



Charging Station

BC3010

The Charging Station is a 10-unit charger for the SafetyTag™. With contact charging, it's quick and easy to charge a SafetyTag: just push it in!

The Charging Station can fully charge a depleted SafetyTag in less than six hours. The Charging Status LED on the SafetyTag blinks green while charging, then turns solid green when fully charged.

Up to four Charging Stations can be daisy-chained together off of one power supply, making infrastructure requirements minimal. Charging Stations can be wall or table-mounted to best suit your environment.



Benefits



POWERFUL

- Contact charging
- Powers 10 SafetyTags
- Drained SafetyTags fully charge in less than 6 hours



FLEXIBLE

- Mount on wall or table (vertical or horizontal)
- Connect up to 4 Charging Stations on one power supply

For What

- Charging SafetyTags

For Who

- SafetyTag users



Specifications

MECHANICAL

Dimensions	Base mounted:
	21 cm (W) x 19 cm (L) x 33.2 cm (H)
Weight	Horizontally table mounted:
	21 cm (W) x 30 cm (L) x 7.6 cm (H)
Mounting Options	Table mount (horizontal or vertical) or wall mount

POWER

AC Adapter	Input: 85-264 VAC, 47/63 Hz
	Safety: thermal, voltage, and power overload protection
Inlet Power	24VDC, 18A
Outlet Power	24VDC 14A

ENVIRONMENTAL

Operating Temperature	-20°C to +60°C
Storage Temperature	-40°C to +85°C
Working Humidity	20 to 95%, non-condensing
Relative Humidity	Up to 95%, non-condensing

DEVICE

Certifications	Pending
-----------------------	---------

Dimension Drawing

